查询IRHE9130供应商

PD - 90881C

International
IOR Rectifier

RADIATION HARDENED POWER MOSFET SURFACE MOUNT (LCC-18)

IRHE9130
100V, P-CHANNEL
REF: MIL-PRF-19500/630
RAD-Hard™ HEXFET®
MOSFET TECHNOLOGY

Product Summary

Part Number	Radiation Level	$R_{DS(on)}$	I_D	QPL Part Number
IRHE9130	100K Rads (Si)	0.30Ω	-6.5A	JANSR2N7389U
IRHE93130	300K Rads (Si)	0.30Ω	-6.5A	JANSF2N7389U



LCC - 18

International Rectifier's RAD-Hard™ HEXFET® MOSFET technology provides high performance power MOSFETs for space applications. This technology has over a decade of proven performance and reliability in satellite applications. These devices have been characterized for both Total Dose and Single Event Effects (SEE). The combination of low Rdson and low gate charge reduces the power losses in switching applications such as DC to DC converters and motor control. These devices retain all of the well established advantages of MOSFETs such as voltage control, fast switching, ease of paralleling and temperature stability of electrical parameters.

Features:

- Single Event Effect (SEE) Hardened
- Low $R_{DS(on)}$
- Low Total Gate Charge
- Proton Tolerant
- Simple Drive Requirements
- Ease of Paralleling
- Hermetically Sealed
- Ceramic Package
- Surface Mount
- Light Weight

Absolute Maximum Ratings

Pre-Irradiation

	Parameter		Units
I_D @ V_{GS} = 12V, T_C = 25°C	Continuous Drain Current	-6.5	A
I_D @ V_{GS} = 12V, T_C = 100°C	Continuous Drain Current	-4.1	
I_{DM}	Pulsed Drain Current ①	-26	
P_D @ T_C = 25°C	Max. Power Dissipation	25	W
	Linear Derating Factor	0.2	W/°C
V_{GS}	Gate-to-Source Voltage	±20	V
E_{AS}	Single Pulse Avalanche Energy ②	165	mJ
I_{AR}	Avalanche Current ①	-6.5	A
E_{AR}	Repetitive Avalanche Energy ①	2.5	mJ
dv/dt	Peak Diode Recovery dv/dt ③	-22	V/ns
T_J	Operating Junction	-55 to 150	°C
T_{STG}	Storage Temperature Range		
	Pckg. Mounting Surface Temp.	300 (for 5s)	
	Weight	0.42 (Typical)	g

For footnotes refer to the last page

Electrical Characteristics @ Tj = 25°C (Unless Otherwise Specified)

	Parameter	Min	Typ	Max	Units	Test Conditions
BV_{DSS}	Drain-to-Source Breakdown Voltage	-100	—	—	V	V_{GS} =0 V, I_D = -1.0mA
$\Delta BV_{DSS}/\Delta T_J$	Temperature Coefficient of Breakdown Voltage	—	-0.112	—	V/°C	Reference to 25°C, I_D = -1.0mA
$R_{DS(on)}$	Static Drain-to-Source On-State Resistance	—	—	0.30	Ω	V_{GS} = -12V, I_D = -4.1A ④
		—	—	0.35		V_{GS} = -12V, I_D = -6.5A ④
$V_{GS(th)}$	Gate Threshold Voltage	-2.0	—	-4.0	V	V_{DS} = V_{GS}, I_D = -1.0mA
g_{fs}	Forward Transconductance	2.5	—	—	S (℧)	V_{DS} > -15V, I_{DS} = -4.1A ④
I_{DSS}	Zero Gate Voltage Drain Current	—	—	-25	μA	V_{DS}= -80V,V_{GS}=0V
		—	—	-250		V_{DS} = -80V, V_{GS} = 0V, T_J = 125°C
I_{GSS}	Gate-to-Source Leakage Forward	—	—	-100	nA	V_{GS} = -20V
I_{GSS}	Gate-to-Source Leakage Reverse	—	—	100		V_{GS} = 20V
Q_g	Total Gate Charge	—	—	45	nC	V_{GS} = -12V, I_D = -6.5A, V_{DS} = -50V
Q_{gs}	Gate-to-Source Charge	—	—	10		
Q_{gd}	Gate-to-Drain ('Miller') Charge	—	—	25		
$t_{d(on)}$	Turn-On Delay Time	—	—	30	ns	V_{DD} = -50V, I_D = -6.5A, V_{GS} = -12V, R_G = 7.5Ω
t_r	Rise Time	—	—	50		
$t_{d(off)}$	Turn-Off Delay Time	—	—	70		
t_f	Fall Time	—	—	70		
$L_S + L_D$	Total Inductance	—	6.1	—	nH	Measured from the center of drain pad to center of source pad
C_{iss}	Input Capacitance	—	1200	—	pF	V_{GS} = 0V, V_{DS} = -25V, f = 1.0MHz
C_{oss}	Output Capacitance	—	290	—		
C_{rss}	Reverse Transfer Capacitance	—	76	—		

Source-Drain Diode Ratings and Characteristics

	Parameter	Min	Typ	Max	Units	Test Conditions
I_S	Continuous Source Current (Body Diode)	—	—	-6.5	A	
I_{SM}	Pulse Source Current (Body Diode) ①	—	—	-26		
V_{SD}	Diode Forward Voltage	—	—	-3.0	V	T_j = 25°C, I_S = -6.5A, V_{GS} = 0V ④
t_{rr}	Reverse Recovery Time	—	—	250	nS	Tj = 25°C, I_F = -6.5A, di/dt ≤ -100A/μs
Q_{RR}	Reverse Recovery Charge	—	—	0.74	μC	V_{DD} ≤ -25V ④
t_{on}	Forward Turn-On Time	Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by L_S + L_D.				

Thermal Resistance

	Parameter	Min	Typ	Max	Units	Test Conditions
R_{thJC}	Junction-to-Case	—	—	5.0	°C/W	
R_{thJPCB}	Junction-to-PC Board	—	19	—		Solder to a copper clad PC Board

Note: Corresponding Spice and Saber models are available on the G&S Website.

For footnotes refer to the last page

International Rectifier Radiation Hardened MOSFETs are tested to verify their radiation hardness capability. The hardness assurance program at International Rectifier is comprised of two radiation environments. Every manufacturing lot is tested for total ionizing dose (per notes 5 and 6) using the TO-3 package. Both pre- and post-irradiation performance are tested and specified using the same drive circuitry and test conditions in order to provide a direct comparison.

Table 1. Electrical Characteristics @ Tj = 25°C, Post Total Dose Irradiation ⑤⑥

	Parameter	100K Rads(Si)[1]		300K Rads (Si)[2]		Units	Test Conditions
		Min	Max	Min	Max		
BV_{DSS}	Drain-to-Source Breakdown Voltage	-100	—	-100	—	V	V_{GS} = 0V, I_D = -1.0mA
$V_{GS(th)}$	Gate Threshold Voltage	- 2.0	- 4.0	-2.0	-5.0		V_{GS} = V_{DS}, I_D = -1.0mA
I_{GSS}	Gate-to-Source Leakage Forward	—	-100	—	-100	nA	V_{GS} = -20V
I_{GSS}	Gate-to-Source Leakage Reverse	—	100	—	100		V_{GS} = 20 V
I_{DSS}	Zero Gate Voltage Drain Current	—	-25	—	-25	µA	V_{DS}=-80V, V_{GS} =0V
$R_{DS(on)}$	Static Drain-to-Source ④ On-State Resistance (TO-3)	—	0.259	—	0.259	Ω	V_{GS} = -12V, I_D =-4.1A
$R_{DS(on)}$	Static Drain-to-Source ④ On-State Resistance (LCC-18)	—	0.30	—	0.30	Ω	V_{GS} = -12V, I_D =-4.1A
V_{SD}	Diode Forward Voltage ④	—	-3.0	—	-3.0	V	V_{GS} = 0V, I_S = -6.5A

1. Part number IRHE9130 (JANSR2N7389U)
2. Part number IRHE93130 (JANSF2N7389U)

International Rectifier radiation hardened MOSFETs have been characterized in heavy ion environment for Single Event Effects (SEE). Single Event Effects characterization is illustrated in Fig. a and Table 2.

Table 2. Single Event Effect Safe Operating Area

Ion	LET	Energy	Range	$V_{DS(V)}$				
	MeV/(mg/cm²))	(MeV)	(µm)	@V_{GS}=0V	@V_{GS}=5V	@V_{GS}=10V	@V_{GS}=15V	@V_{GS}=20V
Cu	28	285	43	-100	-100	-100	-70	-60
Br	36.8	305	39	-100	-100	-70	-50	-40
I	59.8	343	32.6	-60	—	—	—	—



Fig a. Single Event Effect, Safe Operating Area

For footnotes refer to the last page



Fig 1. Typical Output Characteristics



Fig 2. Typical Output Characteristics



Fig 3. Typical Transfer Characteristics



Fig 4. Normalized On-Resistance Vs. Temperature



Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage



Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage



Fig 7. Typical Source-Drain Diode Forward Voltage



Fig 8. Maximum Safe Operating Area



Fig 9. Maximum Drain Current Vs. Case Temperature



Fig 10a. Switching Time Test Circuit



Fig 10b. Switching Time Waveforms



Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case



Fig 12a. Unclamped Inductive Test Circuit



Fig 12b. Unclamped Inductive Waveforms



Fig 12c. Maximum Avalanche Energy Vs. Drain Current



Fig 13a. Basic Gate Charge Waveform



Fig 13b. Gate Charge Test Circuit

Footnotes:

① Repetitive Rating; Pulse width limited by maximum junction temperature.

② V_{DD} = -25V, starting T_J = 25°C, L= 7.8mH Peak I_L = -6.5A, V_{GS} = -12V

③ I_{SD} ≤ -6.5A, di/dt ≤ -430A/μs, V_{DD} ≤ -100V, T_J ≤ 150°C

④ Pulse width ≤ 300 μs; Duty Cycle ≤ 2%

⑤ **Total Dose Irradiation with V_{GS} Bias.** -12 volt V_{GS} applied and V_{DS} = 0 during irradiation per MIL-STD-750, method 1019, condition A.

⑥ **Total Dose Irradiation with V_{DS} Bias.** -80 volt V_{DS} applied and V_{GS} = 0 during irradiation per MIL-STD-750, method 1019, condition A.

Case Outline and Dimensions — LCC-18



NOTES:

1. DIMENSIONING & TOLERANCING PER ANSI Y14.5M–1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information.
Data and specifications subject to change without notice. 02/03